



# Thermo Scientific™ Undercounter Series Refrigerators

Innovative refrigeration solutions for laboratory  
and research needs

# Designed with you in mind



## TSU405 features

- Remote alarm contacts on the undercounter refrigerator, supporting requirements of research for monitoring
- Certified to meet the NSF/ANSI 456 Vaccine Storage standards
- Whisper quiet operation leading to a more comfortable work environment supporting laboratory needs
- Energy Star rated performance meaning lower operating costs
- Green refrigerants supporting global initiatives to reduce green house gas emissions
- Full alarm set, including high/low temperature, door ajar and power fail to support requirements for critical cold storage.

## Clear intuitive display for precise temperature control



## Designed for the following industries



Molecular biology



Vaccines & pharmacies



Laboratory applications



Industrial testing

## Undercounter Series Small Capacity Refrigerator

Temp. range (set point)	Capacity cu. ft. (liters)	Electrical plug	Doors	Shelves	Defrost	Certification	Interior dimensions D x W x H in (D x W x H cm)	Exterior dimensions D x W x H in (D x W x H cm)	Shipping weight lb (kg)	Cat. No.
2-8° C (5° C)	4.5 (40)	230 V, 50 Hz (EU plug)	1 glass	2	Automatic	CE, NSF 456	20.31 x 17.32 x 22.04 (51.59 x 43.99 x 55.98)	25.78 x 20.47 x 32.67 (65.48 x 51.99 x 82.98)	152 (69)	TSU405GV
2-8° C (5° C)	4.5 (40)	230 V, 50 Hz (EU plug)	1 solid	2	Automatic	CE, NSF 456	20.31 x 17.32 x 22.04 (51.59 x 43.99 x 55.98)	25.78 x 20.47 x 32.67 (65.48 x 51.99 x 82.98)	152 (69)	TSU405SV
2-8° C (5° C)	4.5 (40)	230 V, 50 Hz (UK plug)	1 glass	2	Automatic	UKCA, NSF 456	20.31 x 17.32 x 22.04 (51.59 x 43.99 x 55.98)	25.78 x 20.47 x 32.67 (65.48 x 51.99 x 82.98)	152 (69)	TSU405GW
2-8° C (5° C)	4.5 (40)	230 V, 50 Hz (UK plug)	1 solid	2	Automatic	UKCA, NSF 456	20.31 x 17.32 x 22.04 (51.59 x 43.99 x 55.98)	25.78 x 20.47 x 32.67 (65.48 x 51.99 x 82.98)	152 (69)	TSU405SW
2-8° C (5° C)	4.5 (40)	115 V, 60 Hz (NEMA 5-15)	1 glass	2	Automatic	UL, cUL, NSF 456	20.31 x 17.32 x 22.04 (51.59 x 43.99 x 55.98)	25.78 x 20.47 x 32.67 (65.48 x 51.99 x 82.98)	152 (69)	TSU405GA
2-8° C (5° C)	4.5 (40)	115 V, 60 Hz (NEMA 5-15)	1 solid	2	Automatic	UL, cUL, NSF 456	20.31 x 17.32 x 22.04 (51.59 x 43.99 x 55.98)	25.78 x 20.47 x 32.67 (65.48 x 51.99 x 82.98)	152 (69)	TSU405SA



Learn more at [thermofisher.com/tsu](https://thermofisher.com/tsu)

thermo scientific

**For Laboratory Use. It is the customer's responsibility to ensure that the performance of the product is suitable for customers' specific use or application.** © 2025 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. The ENERGY STAR name and mark are trademarks owned by the US EPA. Specifications, terms, and pricing are subject to change. Not all products are available in all countries. Please consult your sales representative for details. **COL12345 0225 EU**